

# The global leader in multi-platform MLPE technology




## ECU-C

### Energy communication unit with production and consumption monitoring

- High frequency metering
- AC power monitoring
- Relay control
- Built-in Wi-Fi
- Single phase or three phase
- ZigBee or PLC models available

The APsystems Gateway, our state-of-the-art Energy Communication Unit (ECU), is the information gateway for APsystems inverters. It collects and transfers module performance data giving you comprehensive monitoring and control over each individual module, optimizing the performance of your solar array.

The ECU-C, designed from the ground up for commercial applications, offers advanced functionality for more data-centric installations, with consumption and production monitoring, contact and relay ports, and high-frequency metering.



210mm(8.3")	
N L3 L2 L1 PE 16-10-18-30-18-30-30-30-30-30-30-30-30-30-30-30-30-30-	
POWER APsystems ON OF OF OF	120mm (4.7")
Port DC RS232 RS485 OK   ØØØØØØØ ØØØ ØØØ ØØØ ØØØ ØØØ   P1/2 P3 P4 P5 G + TX KX G A B G Intermet Signal Oraut	12

### DIMENSIONS

### **ECU-C** Datasheet

### **Communication Interface**

Communication Method	ZigBee 2.4GHz
Ethernet	10/100M Auto-sensing, Auto-negotiation
Integrated Wi-Fi	802.11g/n
Wireless Security	WEP, WPA2-PSK
USB interface	5Vdc-0.5A Output x2
RS232	Standard
RS485	Standard
RJ45	Standard

### **Power Supply**

AC Power Supply	110VAC-277VAC, 50Hz-60Hz Single Phase/ Three Phase
DC Power Supply	12V-16V
Power Consumption	3W

### **Mechanical Data**

Dimensions (W $\times$ H $\times$ D)	210mm x 120mm x 41mm (8.3" x 4.7" x 1.6")
Weight	500g (1.11bs)
Ambient Temperature Range	-40°C to +65°C (-40°F to 149°F)
Cooling	Nature convection - No Fans
Enclosure Environmental Rating	Indoor - IP20 (NEMA 1)

#### **Other Features**

Grid Type	Single Phase / Three Phase
Relay Driver	Control for external AC contact or relay
Digital Input	External control device connection
CT Sensor	High frequency production and consumption metering
Meter Accuracy	Integrated PV production metering (+/- 0.5% via CT) and optional consumption monitoring (+/- 2.5% via CT)
Compliance	

Compliance

IEC/EN61010-1, EN61000-6-1, EN61000-6-2, EN61000-6-3, EN61000-6-4, 2014/30/EU, EN301489-1/-17, EN62479,EN 300328

Specifications subject to change without notice please ensure you are using the most recent update found at latam.APsystems.com *3.8.19* © *All Rights Reserved*