



CHARACTERISTICS



Compact size ideal for any type of use.




Great performance due to its Deep Cycle technology.



Perfect to use as accumulator in photovoltaic installations.

DIMENSIONS



AGM DEEP CYCLE BATTERY 12V 150 AH

DEEP CYCLE SERIES BATTERY

DC series VRLA batteries are superior Deep Cycle design with thick plates, high-density active materials and slightly stronger electrolyte, which can withstand repeated deep cyclic applications. Deep Cycle series batteries are the special design batteries with 10 years floating design life at 25°C. Meet with IEC, BS,JIS and Eurobat standard, UL(MH62092), CE approved.



APPLICATION

- Emergency Power System
- Communication equipment
- Telecommunication systems
- Uninterruptible power supplies
- Power tools
- Marine equipment
- Medical equipment
- Solar and wind power system

GENERAL FEATURES

- Safety Sealing
- Non-spillable construction
- High power density
- Excellent recovery from Deep discharge
- Thick plates and high active materials
- Longer life and low self-discharge design

TECHNICAL SPECIFICATIONS


BATTERY MODEL	Nominal voltage			12V			
	Rated capacity (100 hour rate)			150Ah			
DIMENSION	Cells Per battery			6			
	Length 407 mm	Width 174 mm	Height 209 mm	Total Height 233 mm			
APPROX. WEIGHT	33.5 kg ± 3%						
CAPACITY @ 25°C	10 hour rate (12A, 10.8V)	5 hour rate (19.2A, 10.5V)	3 hour rate (30A, 10.2V)	1 hour rate (72A, 9.6V)			
	120 Ah	96 Ah	90 Ah	72 Ah			
MAX. DISCHARGE CURRENT	1200 A (5 sec.)						
INTERNAL RESISTANCE	Full charged Vat 25°C: Approx. 4.5mΩ						
CAPACITY AFFECTED BY TEMP. (10 HR)	40°C	25°C	0°C	-15°C			
	102%	100%	85%	65%			
SELF DISCHARGE @25°C	After 3 months storage		After 6 months storage	After 12 months storage			
	91%		82%	64%			
CHARGE METHOD @25°C	Cycle Use			Float Use			
	14.1-14.4V (Initial charging current less than 27A)			13.50-13.80V			
CONSTRUCTION	Container	Electrolyte	Separator	Positive	Negative	Safety valve	Terminal
	BS (UL94-HB) / Flame retardant ABS (UL94-V0)	Sulfuric acid	Fiber glass	Lead dioxide	Lead	EPDR	Copper

BATTERY DISCHARGE TABLE


CONSTANT CURRENT (AMP) AND CONSTANT POWER (WATT) DISCHARGE TABLE AT 25 °C

F.V / TIME	5 min	10 min	15 min	30 min	1 hr	2 hr	3 hr	4 hr	5 hr	8 hr	10 hr	20 hr
9.60	A	384.0	253.0	204.0	137.0	72.0	42.0	31.0	24.0	19.8	14.0	6.8
	W	3967.0	2704.0	2189.0	1471.0	778.0	461.0	343.0	270.0	225.1	160.9	79.1
10.20	A	372.0	228.0	192.0	131.0	68.0	40.0	30.0	23.4	19.4	13.7	6.6
	W	3976.0	2551.0	2151.0	1468.0	765.0	462.0	347.0	272.1	226.6	160.1	77.4
10.50	A	360.0	204.0	168.0	122.0	66.0	39.0	29.0	23.0	19.2	13.6	6.6
	W	3933.0	2325.0	1919.0	1409.0	759.0	454.0	341.0	269.6	225.1	159.5	78.0
10.80	A	347.0	193.0	156.0	113.0	63.0	38.0	29.0	22.7	18.7	13.2	6.5
	W	3894.0	2221.0	1800.0	1307.0	738.0	447.0	337.0	267.8	221.3	156.4	77.2
11.10	A	335.0	180.0	144.0	101.0	61.0	37.0	28.0	22.1	18.2	12.8	6.1
	W	3803.0	2090.0	1679.0	1179.0	720.0	440.0	328.0	263.0	217.7	153.8	74.2


Discharge characteristic Curve




Cycle service life in relation to depth of discharge




Relationship between charging voltage and temperature




Constant voltage charging characteristic (0.25CA, at 25°C)




Temperature effects on float life



Self-discharge characteristic




Life characteristics of standby use*



*Testing conditions:
Floating voltage 2.27 to 2.30V/Cell
Ambient temperature 25°C

Charge characteristic Curve for standby use**



**Discharge 100% (0.05CA 20h)
Charge 50% (0.05CA 10h)
Charge Voltage 2.275V/C
Charge Current 0.1CA
Temperature 25°C